

Huhnseal Fastener Type and Naming Table



Swedish Norm	Swedish Name	Huhnseal Abbreviation	English name	DIN norm	Image
Screws					
M6S	Sexkantsskruv	HHS	Hex Head Screw	DIN 931	
M6S	Sexkantsskruv helgängad	HHSF	Hex Head Screw, Fully threaded	DIN 933	
MC6S	Sexkantskruv	SHCS	Socket Head Cap Screw	DIN 912	
MFS	Spårskruv med sänkhuvud	SLFHS	Slotted Flat Head Screw	DIN 963	
MF6S	Sexkantskruv med sänkhuvud	SFHS	Socket Flat Head Screw	DIN 7991	
MT6SS	Stoppskruv med sexkantshål och tapp	SSS DG PT	Socket Set Screw, Dog Point	DIN 915	
MP6SS	Stoppskruv med sexkantshål och plan ände	SSS FL PT	Socket Set Screw, Flat Point	DIN 913	
MSK6SS	Stoppskruv med sexkantshål och skål	SSS C PT	Socket Set Screw, Cup Point	DIN 916	
Washers					
RB	Rundbricka	-	Washer	DIN 125	
FBB	Fjäderbricka	-	Lock Washer	DIN 127	
BR ¹⁾	Gummistålbricka / tätningbricka	-	Sealing Washer	-	
Nuts					
M6M	Sexkantsmutter	-	Hex Nut	DIN 934	
LM6M	Låsexkantsmutter	-	Lock Nut	DIN 985	
MHM	Hatmutter	-	Hex Cap Nut	DIN 1587	
Pins					
CP	Cylindrisk Pinne	-	Dowel Pin	ISO 2338 ²⁾	
KP	Konisk Pinne	-	Taper Pin	DIN 1	
RP	Räffelpinne	GROOVED PIN	Half Length Grooved Pin	DIN 1472	
RP	Räffelpinne	GROOVED PIN	Socket Grooved Pin	DIN 1474	
Retaining rings					
SGA	Spärring för axel	EXT RET RING	External Retaining Ring	DIN 471	
SGH	Spärring för hål	INT RET RING	Internal Retaining Ring	DIN 472	

¹⁾ There is no norm, this is a common trade name. BRT=inch, BRM= metric

²⁾ This is NOT identical to DIN 7. DIN 7 takes the length only over the cylindrical area, ISO 2338 between the ends.